



CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 11/20/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Trade name : CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz
Product code : 1003768
Part number : 05330

1.2. Recommended use and restrictions on use

Use of the substance/mixture : General purpose penetrant

1.3. Supplier

Manufactured or sold by:

CRC Industries, Inc.
885 Louis Dr.
Warminster, PA 18974
United States
T 1-800-556-5074
crcindustries.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300
24-Hour Emergency

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1

Specific target organ toxicity – Single exposure, Category 3, Narcosis
Aspiration hazard Category 1
Hazardous to the aquatic environment – Acute Hazard Category 2
Hazardous to the aquatic environment – Chronic Hazard Category 2

Extremely flammable aerosol. Pressurized container: may burst if heated.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Extremely flammable aerosol.

Pressurized container: may burst if heated

May be fatal if swallowed and enters airways

May cause drowsiness or dizziness

Precautionary statements (GHS US) :

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Avoid breathing mist, vapors, spray.
Use only outdoors or in a well-ventilated area. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area.
If swallowed: Immediately call a poison center or doctor.
Do NOT induce vomiting.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a poison center or doctor if you feel unwell.
Store locked up.
Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Exposure to high temperature may cause can to burst.
Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Distillates (petroleum), hydrotreated light	Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	60 - 80
Naphtha (petroleum), hydrotreated heavy	Naphtha (petroleum), hydrotreated heavy	CAS-No.: 64742-48-9	5 - 10
2-Propanol, 1-(1-methyl-2-propoxyethoxy)-	1-(1-Methyl-2-propoxyethoxy)-propan-2-ol	CAS-No.: 29911-27-1	3 - 7
Carbon dioxide	Carbon dioxide	CAS-No.: 124-38-9	1 - 5
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Distillates (petroleum), solvent-dewaxed heavy paraffinic	CAS-No.: 64742-65-0	1 - 5
Paraffin oils (petroleum), catalytic dewaxed light	Paraffin oils (petroleum), catalytic dewaxed light	CAS-No.: 64742-71-8	1 - 5
Nonane	Nonane	CAS-No.: 111-84-2	0.1 – 1.5

Comments : Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a physician immediately. Do not induce vomiting. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurized container may rupture when exposed to heat or flame.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: This product is a poor conductor of electricity and can become electrostatically charged. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing mist, vapors, spray.

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Exposure to high temperature may cause can to burst. Wear personal protective equipment. Avoid breathing mist, vapors, spray. Use only outdoors or in a well-ventilated area. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not get in eyes, on skin, or on clothing. For product usage instructions, see the product label.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Level 3 Aerosol. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
- Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbon dioxide (124-38-9)	
USA - OSHA - Occupational Exposure Limits	
Local name	Carbon dioxide
OSHA PEL TWA	9000 mg/m ³
	5000 ppm

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon dioxide (124-38-9)

Regulatory reference (US-OSHA)

OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves such as: Neoprene or nitrile rubber gloves

Eye protection:

Safety glasses with side shields

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Light Amber
Odor : Petroleum
Odor threshold : No data available
Melting point : Not applicable
Freezing point : -121 °F estimated
Boiling point : 315 °F estimated
Flammability (solid, gas) : Extremely flammable aerosol.
Explosion limits : Lower explosion limit: 0.6 % estimated
Upper explosion limit: 20.4 % estimated
Flash point : 141 °F Setflash
Auto-ignition temperature : 401 °F estimated
Decomposition temperature : No data available
pH : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Solubility : No data available
Partition coefficient n-octanol/water (Log Pow) : No data available
Vapor pressure : No data available
Density and/or relative density
Density : 6.831 lb/gal Concentrate
Relative density : 0.82 Concentrate
Particle characteristics : No data available

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1)	: No data available
Relative vapor density at 20°C	: > 4 (air=1) estimated
Molecular mass	: No available data
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: may burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung edema.
Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	2.18 mg/l Source: IUCLID

Paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	---

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates (petroleum), hydrotreated light (64742-47-8)	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	> 5.2 mg/l Source: IUCLID
Nonane (111-84-2)	
LD50 oral rat	> 5000 mg/kg Source: ECHA
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	17 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 14 - 21
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	> 5610 mg/l
2-Propanol, 1-(1-methyl-2-propoxyethoxy)- (29911-27-1)	
LD50 dermal rabbit	≥ 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Guideline: other:, Guideline: other:
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Carbon dioxide (124-38-9)	
pH	3.2 Source: HSDB
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Carbon dioxide (124-38-9)	
pH	3.2 Source: HSDB
Respiratory or skin sensitization	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
STOT-single exposure	: May cause drowsiness or dizziness.
Nonane (111-84-2)	
STOT-single exposure	: May cause drowsiness or dizziness.
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (oral, rat, 90 days)	750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Nonane (111-84-2)	
NOAEL (oral, rat, 90 days)	100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapor, 90 days)	24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (subchronic, oral, animal/male, 90 days)	100 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
2-Propanol, 1-(1-methyl-2-propoxyethoxy)- (29911-27-1)	
NOAEL (oral, rat, 90 days)	500 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: No data available
Nonane (111-84-2)	
Viscosity, kinematic	1.008 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
Viscosity, kinematic	< 1 mm ² /s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Carbon dioxide (124-38-9)	
LC50 - Fish [1]	35 mg/l Source: HSDB
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates (petroleum), hydrotreated light (64742-47-8)	
LC50 - Fish [1]	2.4 mg/l Source: ECOTOX
Nonane (111-84-2)	
LC50 - Fish [1]	1.125 mg/l Source: QSAR, ECHA
EC50 - Crustacea [1]	0.2 mg/l Source: ECHA
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
LC50 - Fish [1]	2200 mg/l Source: IUCLID
LC50 - Other aquatic organisms [1]	2.6 mg/l Source: IUCLID
EC50 - Other aquatic organisms [1]	> 1000 mg/l waterflea
2-Propanol, 1-(1-methyl-2-propoxyethoxy)- (29911-27-1)	
LC50 - Fish [1]	2153 mg/l Source: ECOSAR
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	260.5 mg/l Source: ECOSAR

12.2. Persistence and degradability

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz	
Persistence and degradability	No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Carbon dioxide (124-38-9)	
Partition coefficient n-octanol/water (Log Pow)	0.83 Source: ISCS
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Distillates (petroleum), hydrotreated light (64742-47-8)	
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID
Nonane (111-84-2)	
Partition coefficient n-octanol/water (Log Pow)	5.65 Source: HSDB
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID
2-Propanol, 1-(1-methyl-2-propoxyethoxy)- (29911-27-1)	
Partition coefficient n-octanol/water (Log Pow)	0.64 Source: episuite

12.4. Mobility in soil

No additional information available

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods




Regional waste regulation : Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations : Contents under pressure. Empty container can be recycled. Full or partially-full aerosol cans can be treated as universal waste.
Hazardous waste code : Possible RCRA waste code includes:
D001: Ignitable Waste

However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.

Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
Aerosols, flammable, (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, flammable (Limited quantity)
14.3. Transport hazard class(es)		
LTD QTY	LTD QTY	LTD QTY Y
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Marine Pollutant Exception		

14.6. Special precautions for user

DOT
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
UN-No.(DOT) : UN1950
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Class (IMDG) : 2.1 - Flammable Gas

Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

Packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

IATA

Class (IATA) : 2.1 - Gases : Flammable

PCA Excepted quantities (IATA) : E0

PCA Limited quantities (IATA) : Y203

PCA limited quantity max net quantity (IATA) : 30kgG

PCA packing instructions (IATA) : 203

PCA max net quantity (IATA) : 75kg

CAO packing instructions (IATA) : 203

CAO max net quantity (IATA) : 150kg

Special provision (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Toxic Substances Control Act (TSCA)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Name	CAS-No.	Commercial status	Flags
Carbon dioxide	124-38-9	Active	
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	Active	
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Active	

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Active	
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	Active	
Distillates (petroleum), hydrotreated light	64742-47-8	Active	
Nonane	111-84-2	Active	T
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Active	
9-Octadecenoic acid (9Z)-	112-80-1	Active	
2-Propanol, 1-(1-methyl-2-propoxyethoxy)-	29911-27-1	Active	
Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S			
Nonane	CAS-No. 111-84-2	0.1 – 1.5%	

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substance

CERCLA Section 103 (40CFR302.4)	Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.
---------------------------------	---

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986)

Section 302 Extremely Hazardous Substance

Not listed

Section 304 Emergency Release Notification

Not listed

Sections 311/312 Hazard Classification

Not listed

Section 313 (TRI Reporting)

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

No additional information available


CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

California Proposition 65

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

U.S. - California - Proposition 65 - Carcinogens List	
Ethylbenzene(100-41-4)	XLISTED
Benzene(71-43-2)	XLISTED
Naphthalene(91-20-3)	XLISTED

U.S. - California - Proposition 65 - Reproductive Toxicity - Male	
Benzene(71-43-2)	XLISTED

U.S. - California - Proposition 65 - Developmental Toxicity	
Toluene(108-88-3)	XLISTED
Benzene(71-43-2)	XLISTED

State Regulations

Component	State Regulations
Carbon dioxide(124-38-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Paraffin oils (petroleum), catalytic dewaxed heavy(64742-70-7)	U.S. - Massachusetts - Right To Know List
Paraffin oils (petroleum), catalytic dewaxed light(64742-71-8)	U.S. - Massachusetts - Right To Know List
Nonane(111-84-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
9-Octadecenoic acid (9Z)-(112-80-1)	U.S. - Pennsylvania - RTK (Right to Know) List

15.4 Other Regulatory Information

Volatile organic compound (VOC) regulation

EPA

VOC content (40 CFR 51.100(s))	97.2 %
Consumer products (40 CFR 59, Subpt. C))	Not regulated.

CRC® Ultra Screwloose® Super Penetrant, 11 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

State

Consumer products	This product is regulated as a Penetrant. This product is compliant for use in all 50 states.
VOC Content (CA)	24.1 %
VOC Content (OTC)	24.1 %

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Author : Angelina Cibulskis
Other information : CRC# 00575H/1002602.

Safety Data Sheet (SDS), USA, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Inc.